DSP7064 6.5" 2-Way Wall Mount Speaker



Features

Official

Support Partner

- Compact and classic full-range, all-purpose wall mount speaker, exceptional reproduction of music and speech for indoor commercial background and foreground applications;
- 2-way system, with integrated passive crossover network and tweeter overload protection;
- 6.5" high output woofer and 1" voice coil compression driver with 130° horn, brilliant audio with wide controlled coverage pattern for vertical or horizontal mounting;
- ➤ 40 Watt RMS running to 80 Watt maximum, efficient high power output for clear and powerful sound;
- Simple and flexible installation, U bracket and M6 screw knob with integrated Recessed carry handles.



Description

The full-range speakers are designed for professional music and speech reproduction in an impressive array of background and foreground audio applications. The classic and robust design suits a variety of commercial interiors. Ideal for single-source audio in smaller venues, or straightforward integration into multi arrays.

Specification

| System Specifications | |
|--------------------------|---------------------|
| LF Unit | 6.5 inch * 1 |
| HF Driver | 1 inch * 1 |
| Impedance(AC) | 8Ω |
| Output SPL | 89±3dB |
| Resonant Freq.(FO) | 57±15Hz |
| Freq. Range | FO~20KHz±3dB |
| Transformer power | 40W |
| Input power | 8Ω-0-40W-20W-10W-5W |
| Dimension (H*W*D) | 285*195*180mm3. |
| Net Weight | 3.5kg |
| Package | 2 pcs per carton |
| Out carton size(L*W*H) | 570*300*375mm |
| Inner carton size(L*W*H) | 275*270*345mm |