

# DSP1530 Ceiling Speaker

## Features

- Built-in 100v/70v transformer
- Max SPL: 99±2dB
- High sensitivity: 90±2dB
- Effective Freq: 83Hz -20kHz
- Made of highquality engineering plastic
- Equipped with clamps for mounting
- Long life, sound clear and sonorousness.
- long-term durability



## Description

- The DSP1530 is a ceiling speaker with a 70v/100v transformer built in. The 70v/100v transmission is realized in a high-voltage, low-current mode, which makes longer distance transmission and parallel connection of multiple loudspeakers possible.
- The built-in 4.5" speaker driver is designed of wide frequency response 83Hz-20Hz, It is made of high quality engineering plastic, which ensures long-term durability, and will never be out of shape or fading; Spring clip clamp makes the easy and secure installation; Driver surround excellent damping, long life, clear and sonorous sound.
- It is an ideal choice for industrial and commercial applications in hotel, school, office and factory where background music and paging is needed.

## Specification

Model	DSP1530
Speaker Unit	4.5"x1
Rated Power	1.5W
Max Power	3.0W
Rated Input	70/100V
Sensitivity	90±2dB
Max SPL	99±2dB
FREQ.RESP	83Hz -20kHz
Hole for mounting	Ø150--Ø155mm
Weight	0.45kg