

DSP5211L/DSP5211CL

Ceiling Speaker



Description

DSP5211L/DSP5211CL Ceiling Speaker is a coaxial two frequency speaker, with a wide range of sound diffusion. large output power. easy installation, which can reproduce the voice and music.

It's an ideal choice for you when you are in need of a ceiling speaker requiring perfect sound quality. This product is widely used in schools, offices, cafes, hospitals, hotels, and shopping malls. By the way, DSP5211CL is a ceiling speaker with back cover whereas DSP5211L without.

Features

- Fashionable thin-edge planer and the carbon alloy aluminum mesh design with the RAL white coating to match with any indoor place perfectly;
- 6.5" bass unit with magnetic circuit encapsulated of special engineering plastic process;
- Concentric 0.75" tweeter provides clear and round treble; the diffraction of a high profile provides a broad, uniform coverage;
- Meet the IEC 268-5 power handling capacity (PHC) standard;
- Run continuously for 100 hours and carry out simulating acoustic feedback exposure (SAFE) test;
- Bear double rated powers within a short period to ensure its high reliability under extreme conditions, prolong its service life, and reduce the possibility of occurrence of fault or degradation;
- Powerful clip design, durable and reliable, easy to install;

Specification

Model	DSP5211L	DSP5211CL
Drive Units	6.5"*1	0.75"*1
RMS	10W	
Impedance	8Ω	
Sensitivity(1m, 1W)	93±2dB	
Max S.P.L. (1m)	103±2dB	
Freq. Res.	90Hz-18KHz	
Opening Diameter	Φ168-172mm	
Dimension	Φ190*80mm	Φ190*105mm
Weight	0.8Kg	0.9Kg